

4" Submersible Pumps



The standard FPS 4400 4" submersible pump features the new TRI-SEAL floating stage system. This new stage system further improves efficiency and protects against wear when pumping abrasives (sand). All FPS 4400 pumps are unconditionally guaranteed against sand locking in abrasive well conditions for one full year. For details on how to become a registered dealer and receive a 5-year warranty, contact your local distributor.

Features:

- 300 series stainless steel hub floats with the impeller maintaining a positive seal
- Phenolic washer provides downthrust protection
- Celcon® impeller provides high efficiency performance and abrasion resistance
- Noryl®** diffuser and disc proven abrasion resistant material
- Floating stage design allows impeller to float independently
- Removable, spring-loaded check valve
- Maximum water temperature: 120 °F
- Ceramic shaft sleeve and rubber discharge bearing protect shaft and eliminate sand wear
- Powered by Franklin Electric corrosion resistant
 4" submersible motors
- * Celcon® is a Registered Trademark of the Celanese Corporation.
- ** Noryl® is a Registered Trademark of G.E.


Patented impeller hub seal system seals radially and axially to prevent fluid recirculation, providing high performance in the harshest conditions.

stered

Phenolic washer provides axial sealing as impeller floats in the stage

Seal 1







TRI-SEAL™ Floating Stage System

U.S. Patent No. 7,290,984

Ordering and performance data available online at www.franklin-electric.com/pumps/





400 East Spring St., Bluffton, IN 46714 Tel: 260.824.2900 • Fax: 260.824.2909

www.franklin-electric.com