

F SERIES

FAHRENHEIT** PUMPS SUBMERSIBLES FOR HOT LIQUIDS



ENGINEERED FOR SUBMERSIBLE PUMPING CORROSIVE AND NON-CORROSIVE, CLEAR OR SOLIDS LADEN LIQUIDS UP TO 190 DEGREES FAHRENHEIT

- Beverage, bottling plants
- · Dairy product processing


- Poultry, meat processing
- Chemical, pharmaceuticals

And sumps where liquids are too hot for conventionally built submersible pumps.

FAHRENHEIT™ PUMPS


BJM F SERIES Pumps Submersible pumps built for long life pumping HOT LIQUIDS

• High temperature rated seals, power cords, O-rings & gaskets




SUMP PUMPS: 2 - 4", to 650 gpm and 140 ft head

J-F Series: Cast Iron / 304SS • JX-F Series: All 316SS





SHREDDER PUMPS: 2 - 6", to 900 gpm, 100 ft head
SK-F Series: Cast Iron / 304SS • SKX-F Series: All 316SS




SLURRY PUMPS: 3-6", to 1690 gpm, 105 ft head **KZN-F** Series: Hi Chrome / Cast Iron

WARNING: NOT FOR USE IN ANY FLAMMABLE LIQUIDS.






SUMP PUMPS: 2-4", to 650 gpm and 140 ft head
JH-F Series: Cast Iron / 304SS • JXH-F Series: All 316SS



NON-CLOG PUMPS: 2 - 4", to 600 gpm, 140 ft head S-F Series: Cast Iron / 304SS • \$X-F Series: All 316SS



PORTABLE TOP DISCHARGE: 2", to 110 gpm, 70 ft head **RX-F** Series: All 316SS

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



123 Spencer Plain Road P.O. Box 1138 Old Saybrook, CT 06475

Tel: (860)-399-5937 Toll Free: (877)-BJM-PUMP Fax: (860)-399-7784 Web: www.bjmpumps.com Distributor: